

Self-service out of the box with Windows OS

Introducing the Samsung Kiosk with Windows OS: a compact, modern and eye-catching kiosk to provide reliable performance in any business location. Samsung Kiosk offers a variety of customer payment options including credit card, barcode, QR code and NFC, along with a built-in printer system with no additional peripherals needed. It can be installed on a countertop, on a floor stand, or be mounted on a wall. Plus, with built-in Windows 10 IoT Enterprise OS, it supports enhanced compatibility with various 3rd party devices and services to integrate and boost business operations.

Key features



Windows 10 IoT Enterprise OS

Samsung Kiosk operating on Windows enables flexible connection with versatile devices and services, making it suitable for a wide array of business use cases.



Intel® Core™ Processors

Powered by 11th Gen Intel® Core™ Processor, Samsung Kiosk built on Windows OS features high performance computing power for flexible, stable, and enhanced capabilities.



All-in-One Solution

Samsung Kiosk is an all-in-one solution without the need for an external PC.



Modular Functionality

Samsung Kiosk provides a variety of payment options including credit card, barcode, QR code and NFC, along with a built-in printer.



Stylish Look

Samsung Kiosk's stylish, compact design blends naturally into any store interior.



Optional Stand

Along with optional stand, Samsung Kiosk offers three installation types — countertop, floor stand and wall-mounting — for optimized space saving.

Specifications

Model				KMC-W		
		Diago	nal Size		24"	
Display Part			rpe		ADS	
				FHD (1,920 x1,080)		
		Resolution Brightness (Typ.)		250cd (without glass)		
	Panel	Contrast Ratio (Typ.)		250ca (without glass)		
		Viewing Angle (H/V)		178/178		
		Response Time (G-to-G)		14ms (Typ.)		
		Operation Hour		16/7		
	Touch		rpe	Capative		
	Sound		er Type	Built in Speaker (3W x 1)		
		WiFi		Wi-Fi USB Adapter Included		
	Display Connectivity	Input		N/A		
		Input USB		USB x1 (Service purpose)		
		Output	Touch Out	Touch Out x1 (Service purpose)		
		Bi-direction		One connect port (44 Pin)		
		External	Control	N/A		
		Orientation		Portrait		
		H/W		Antibacterial PEF Film (except Canada, India, CIS;Russia/Ukraine/Uzbekistan/Kazakhstan/Mongolia), 1 Point Touch		
		Special	Platform	Celeron	i3	i5
			Processor	6305E 1.8GHz Dual-Core CPU	i3-1115G4E 2.2GHz Dual-Core CPU	i5-1145G7E 1.5GHz Quad-Core CPU
		Internal Player (Embedded H/W)	On-Chip Cache			
			Memory	4MB Intel® Smart Cache	6MB Intel® Smart Cache	8MB Intel® Smart Cache
			Clock Speed	1.8GHz	2.2GHz	1.5GHz
	Features		Main Memory			
			Interface		8GB, LPDDR4X, 4266Mbps	
				Graphic resolution : 1,920 x 1,080 Output resolution : 1,920 x 1,080		
			Graphics			
			<u></u>	(Scale up from graphic processing result.) 25GB SSD		
			Storage	N/A		
			IO Ports			
			Operating System	Windows 10 IoT Enterprise LTSC (Microsoft)		
	Mechanical Spec	Dimension (mm / in.)	Set	334.4 (W) x 547.9 (H) x 48.8 (D) mm / 13.1 (W) x 21.5 (H) x 1.9 (D) in.		
			Package	419 (W) x 620 (H) x 122 (D) mm / 16.5 (W) x 24.4 (H) x 4.8 (D) in.		
		Weight (kg / lbs.)	Set	4.3 kg / 9.5 lbs.		
		Weight (kg / tbs./	Package	5.7 kg /12/5 lbs.		
Connection	Connection Box Connectivity		Input USB USB x3			
		Bi-direction			One connect port (44 Pin)	
		External				
	Peripheral devices		Type	Thermal		
		Receipt Printer	Printing speed	250mm/sec		
			Cutting	Automatic (Support Full cut, Partial cut)		
			Paper support	Support 80mm paperroll, 20~83mm paperwidth, 0.05~0.12mm paperthickness		
		QR/Barcode Reader	Supported dimension	10, 2D		
Box Part			Readability	Mobile screen and printed barcodes		
BOX Part			Supported format	UPC-A, UPC-E, EAN-8, EAN-13, Code 128, Code 39, Code 93, Interleaved 2 of 5, GS1 DataBar, Codabar, QR		
		Compatible Card Readers		VeriFone, Ingenico, CloverFlex, PAX, ID Tech, Magtek, Stripe, Square, Equinox		
		EFT Terminal Cradle		Support Verifone P400/connected via RS232C		
		Set		334.4 (W) x 389.6 (H) x 236.5 (D) mm / 13.1 (W) x 15.3 (H) x 9.3 (D) in.		
	Mechanical Spec	Dimension (mm / in.)	Package	428 (W) x 471 (H) x 316 (D) mm / 16.8 (W) x 2.8 (H) x 12.4 (D) in.		
			Set	426 (W) x 471 (n) x 316 (D) 11111 / 10.6 (W) x 2.6 (n) x 12.4 (D) 111. 7.4 kg / 16.3 lbs.		
		Weight (kg / lbs.)	Package	7.4 kg / 10.5 tus. 9.1 kg / 20 lbs.		
		T.	ре		External Adapter	
			Supply		AC100~240V 50/60Hz	
		Fower	Max[W/h]	TBD	88	TBD
	Power		Rating[W/h]	TBD	80	TBD
		Power Consumption				
			Stand-by[W/h]	TBD	0.5	TBD TBD
			BTU[W/h] Set	TBD	300.08	
		Dimension (/:-)	Ser	334.4 (W) x 733 (H) x 236.5 (D) mm / 13.1 (W) x 28.9 (H) x 9.3 (D) in.		
		Dimension (mm / in.)		13.2 kg / 29.1 lbs.		
assamble d		Weight (kg / lbs.)	Set			
	Machanical	Weight (kg / lbs.)	Set olor		GRAY WHITE	
Assembled Set	Mechanical	Weight (kg / lbs.) Co Protecti	Set olor on Glass		GRAY WHITE Yes	
	Mechanical Spec	Weight (kg / lbs.) Co Protecti Sta	Set olor on Glass and		GRAY WHITE Yes Yes	
		Weight (kg / lbs.) Co Protecti Sti Media Playe	Set olor on Glass and r Option Type		GRAY WHITE Yes Yes N/A	
		Weight (kg / lbs.) Co Protecti St. Media Playe Rot.	Set on Glass and r Option Type ation		GRAY WHITE Yes Yes N/A N/A	
		Weight (kg / lbs.) Cc Protecti St: Media Playe Rot. Power Cai	Set on Glass on Office of the second of th		GRAY WHITE Yes Yes N/A N/A 1.5m	
	Spec	Weight (kg / lbs.) Co Protecti St Media Playe Rot Power Ca Operating	Set olor on Glass and r Option Type ation ble Length lemperature		GRAY WHITE Yes Yes N/A N/A 1.5m 0°C-40°C	
		Weight (kg / lbs.) Co Protecti St Media Playe Rot Power Ca Operating	Set olor on Glass and r Option Type ation ble Length iemperature nidity		GRAY WHITE Yes Yes N/A N/A 1.5m 0°C - 40°C 10-80%	
	Spec Operation	Weight (kg / lbs.) Co Protects Sti Media Playe Rot. Power Ca Operating 1 Hun	Set olor on Glass and r Option Type ation ble Length lemperature		GRAY WHITE Yes Yes N/A N/A 1.5m 0°C−40°C 10−80% Floor Stand	
	Spec	Weight (kg / lbs.) Co Protecti St Media Playe Rot Power Ca Operating	Set olor on Glass and r Option Type ation ble Length iemperature nidity		GRAY WHITE Yes Yes N/A N/A 1.5m 0°C - 40°C 10-80%	
	Spec Operation	Weight (kg / lbs.) Co Protects Sti Media Playe Rot. Power Ca Operating 1 Hun	Set olor on Glass and r Option Type ation ble Length remperature hidity Stand		GRAY WHITE Yes Yes N/A N/A 1.5m 0°C−40°C 10-80% Floor Stand VESA 200*200	
	Spec Operation	Weight (kg / lbs.) Co Protects Sti Media Playe Rot. Power Ca Operating 1 Hun	Set olor on Glass and r Option Type ation ble Length remperature hidity Stand		GRAY WHITE Yes Yes N/A N/A 1.5m 0°C−40°C 10−80% Floor Stand	
	Spec Operation	Weight (kg / lbs.) Co Protects Sti Media Playe Rot. Power Ca Operating 1 Hun	Set olor on Glass and r Option Type ation ble Length femperature hidity Stand Mount		GRAY WHITE Yes Yes N/A N/A 1.5m 0°C-40°C 10-80% Floor Stand VESA 200*200 Stand	13.9 (D)io
	Spec Operation Others	Weight (kg / lbs.) Co Protects Sti Media Playe Rot. Power Ca Operating 1 Hun	Set olor on Glass and r Option Type attion ble Length femperature nidity Stand Mount Set		GRAY WHITE Yes Yes N/A N/A 1.5m 0°C-40°C 10-80% Floor Stand VESA 200*200 Stand 0 (W) x 929.7 (H) x 324.3 (D) mm / 17.7 (W) x 36.6 (H) x	
	Spec Operation	Weight (kg / lbs.) Co Protecti St Media Playe Rot. Power Ca Operating 1 Hun	Set on Glass and r Option Type attion ble Length femperature idity Stand Mount Set Package		GRAY WHITE Yes Yes N/A N/A 1.5m 0°C- 40°C 10-80% Floor Stand VESA 200*200 Stand) (W) x 929.7 (H) x 324.3 (D) mm /177 (W) x 36.6 (H) x 25 (W) x 10,17 (H) x 389 (D) mm /8.8 (W) x 40 (H) x 15	
	Spec Operation Others	Weight (kg / lbs.) Co Protecti St Media Playe Rot. Power Ca Operating 1 Hun	Set olor on Glass and r Option Type attion ble Length femperature nidity Stand Mount Set		GRAY WHITE Yes Yes N/A N/A 1.5m 0°C-40°C 10-80% Floor Stand VESA 200*200 Stand 0 (W) x 929.7 (H) x 324.3 (D) mm / 17.7 (W) x 36.6 (H) x	

Product Support 1-866-SAM4BIZ

SAMSUNG